

11x30 Aluminum Communications Shelters

- Aluminum Equipment Shelters
- 11' x 30' x 9'I.D.—16,500 lbs w/o customer equipment
- 200 Amp Electrical Service
- Distribution Panel (120/240 Volt, 1phase, 60Hz)
- Disconnect Switch
- 12 x 12 Alarm Panel
- Rectifier Drops; Quad Receptacles; Four Corner Ground Penetrations
- 4ft Fluorescent Lighting Fixtures, Emergency Light, Exterior Light
- Telco Entry in Floor; Equipment Support Angles on Wall
- 12" Cable Tray—Gray Painted—Approximately 80feet
- HVAC Units—Redundant 4Ton—Liebert or Bard with Lead Lag Controller
- Ballistic Liner—11GA Steel in Shelter Walls, 12 x 12 x 1/8" Conductive Tile, Aluminum Battery Support Plate
- 3/0 x 7/0 Aluminum Door (w/Ballistic Liner) with Stainless Steel Hinges and 3pt Door Locking Hardware
- Structural Design: Wind Load: 100mph; Roof Load: 50psf; Floor Loading: 250psf; Seismic: Zone 4
- Forklift Tubes
- 3" O.D. Tow Pipe on each end

Sale Price: TDW ½ Price Discount – Call For Details



Your Telecom Connection. Your Bottom Line.



Your Telecom Connection. Your Bottom Line.